

NITRILE 42

POWDER FREE NITRILE EXAMINATION GLOVES

PRODUCT INFORMATION

Description	:	Disposable Nitrile Examination Gloves, Powder Free, Non-sterile (M=4.2 gram ± 0.3)
Intended Use	:	For Medical Use/ For Food Contact Use/ For General Use
Primary Material	:	Acrylonitrile Butadiene Synthetic Rubber Latex
Latex Protein Content	:	Latex-Free

Physical Dimensions	:	Glove Size			ASTM D6319	EN 455
		Length (mm)			270 min.	270 min.
		Width (mm)	Extra-Small		75 ± 10	75 ± 10
			Small		80 ± 10	80 ± 10
			Medium		95 ± 10	95 ± 10
			Large		110 ± 10	110 ± 10
			Extra-large		≥ 110	≥ 110
		Thickness-single wall (mm)	Cuff		min. 0.05	min. 0.05
			Palm		min. 0.05	min. 0.05
			Finger		min. 0.05	min. 0.05

Physical Properties	:	Criteria			ASTM D6319	EN 455
		Elongation (%)	Before Aging		min. 500	min. 500
			After Aging		min. 400	min. 500
		Tensile Strength	Before Aging		min. 14 (MPa)	6.0 N
			After Aging		min. 14 (MPa)	6.0 N

Color	:	Royal Blue
Size	:	Extra-Small; Small; Medium; Large and Extra-Large
Design and Feature	:	Ambidextrous, Straight Fingers, Finger-Textured, Beaded Cuff, Colour
Packing	:	100 Pieces Gloves per Dispenser, 10 Dispensers Per Carton
Powder	:	No Powder Lubricant Added
Performance	:	Gloves are sampled at random and inspected in accordance with ISO2859-1 based on batch size.

Requirements	:	Criteria	ASTM D6319		EN 455	
			Insp.Level	AQL	Insp.Level	AQL
		1000ml Water Leak Test	G-1	2.5	G-1	1.5
		Physical Properties	S-2	4.0	S-2	4.0
		Dimension	S-2	4.0	S-2	4.0
		Visual Inspection	S-4	4.0	S-4	4.0

Storage	:	Storage in a controlled cool and dry environment
Shelf-life	:	5 years from date of manufacturing
Product Conformance	:	Meets/Exceeds European Standards EN 455 Part 1~4
	:	Meets/Exceeds European Standards EN 420 & EN 16523
	:	Meets/Exceeds European Standards EN 374 Part 1,2 & 5
	:	Meet the Standards of ASTM D6319
Quality Assurance	:	Manufactured under ISO 9001 & ISO 13485 Quality Systems